

TABLE OF CONTENTS

I. INTRODUCTION 1

 I.1 THE MASSACHUSETTS ESTUARIES PROJECT APPROACH 6

 I.2 SITE DESCRIPTION 9

 I.3 NUTRIENT LOADING 12

 I.4 WATER QUALITY MODELING 13

 I.5 REPORT DESCRIPTION 14

II. PREVIOUS STUDIES RELATED TO NITROGEN MANAGEMENT 15

III. DELINEATION OF WATERSHEDS 24

 III.1 BACKGROUND 24

 III.2 SESACHACHA POND CONTRIBUTORY AREAS 24

IV. WATERSHED NITROGEN LOADING TO EMBAYMENT: LAND USE, STREAM INPUTS, AND SEDIMENT NITROGEN RECYCLING 27

 IV.1 WATERSHED LAND USE BASED NITROGEN LOADING ANALYSIS 27

 IV.1.1 Land Use and Water Use Database Preparation 28

 IV.1.2 Nitrogen Loading Input Factors 30

 IV.1.3 Calculating Nitrogen Loads 34

 IV.2 ATTENUATION OF NITROGEN IN SURFACE WATER TRANSPORT 38

 IV.2.1 Background and Purpose 38

 IV.3 BENTHIC REGENERATION OF NITROGEN IN BOTTOM SEDIMENTS 38

 IV.3.1 Sediment-Watercolumn Exchange of Nitrogen 38

 IV.3.2 Method for determining sediment-watercolumn nitrogen exchange 39

 IV.3.3 Rates of Summer Nitrogen Regeneration from Sediments 42

 Sesachacha Pond 44

V. HYDRODYNAMIC MODELING 47

 V.1 INTRODUCTION 47

 V.1.1 System Physical Setting 47

 V.1.2 System Hydrodynamic Setting 48

 V.2 GEOMORPHIC AND ANTHROPOGENIC EFFECTS TO THE SYSTEM 49

 V.2.1 Pond Management Practices 49

 V.2.2 Shoreline Change Analysis 50

 V.3 HYDRODYNAMIC FIELD DATA COLLECTION AND ANALYSIS 51

 V.3.1. Bathymetry 53

 V.3.2 Tide Data 53

 V.4 HYDRODYNAMIC MODEL DEVELOPMENT 53

 V.4.1 Modeling flow through a breach 54

 V.4.2 Modeling the breach at Sesachacha Pond 59

 V.4.3 RMA2 model theory 59

 V.4.4 RMA2 model development 60

 V.5. FLUSHING CHARACTERISTICS 62

VI. WATER QUALITY MODELING 63

 VI.1 DATA SOURCES FOR THE MODEL 63

 VI.1.1 Hydrodynamics and Tidal Flushing in the Embayments 63

 VI.1.2 Nitrogen Loading to the Embayments 63

VI.1.3 Measured Nitrogen Concentrations in the Embayments.....	64
VI.2 MODEL DESCRIPTION AND APPLICATION	64
VI.2.1 Model Formulation.....	65
VI.2.1.1 Dispersion Model.....	65
VI.2.1.2 Mass Balance Model.....	66
VI.2.2 Boundary Condition Specification	67
VI.2.3 Development of Present Conditions Model.....	67
VI.2.4 Total Nitrogen Model Verification	70
VI.2.5 Build-Out and No Anthropogenic Load Scenarios.....	72
VI.2.5.1 Build-Out.....	72
VI.2.5.2 No Anthropogenic Load	73
VII. ASSESSMENT OF EMBAYMENT NUTRIENT RELATED ECOLOGICAL HEALTH.....	75
VII.1 OVERVIEW OF BIOLOGICAL HEALTH INDICATORS.....	75
VII.2 BOTTOM WATER DISSOLVED OXYGEN.....	76
VII.3 EELGRASS DISTRIBUTION - TEMPORAL ANALYSIS.....	81
VII.4 BENTHIC INFAUNA ANALYSIS	81
VIII. CRITICAL NUTRIENT THRESHOLD DETERMINATION AND DEVELOPMENT OF	
 WATER QUALITY TARGETS	84
VIII.1 ASSESSMENT OF NITROGEN RELATED HABITAT QUALITY	84
VIII.2 THRESHOLD NITROGEN CONCENTRATIONS	85
VIII.3 DEVELOPMENT OF TARGET NITROGEN LOADS	86
IX. REFERENCES	91

LIST OF FIGURES

Figure I-1. Location of the Sesachacha Pond system, Island of Nantucket, Town of Nantucket, Massachusetts. Sesachacha Pond is a great salt pond, historically maintained by periodic breaching of the barrier beach to allow exchange with Atlantic Ocean waters..... 1

Figure I-2. Study region for the Massachusetts Estuaries Project analysis of the Sesachacha Pond System. Tidal waters enter the Pond from the Atlantic Ocean during periodic openings of the barrier beach. Freshwaters enter from the watershed primarily through direct groundwater discharge and direct precipitation. 2

Figure I-3. Sesachacha Pond bathymetry depicting major basins, Town of Nantucket, Massachusetts (EIR 1989). 4

Figure I-4. Massachusetts Estuaries Project Critical Nutrient Threshold Analytical Approach 11

Figure II-1. Town of Nantucket Water Quality Monitoring Program sampling stations for Sesachacha Pond as provided by the Town of Nantucket Marine Department..... 23

Figure III-1. Watershed delineations for the Sesachacha estuary system..... 25

Figure IV-1. Land-use in the Sesachacha Pond watershed. The watershed is completely contained within the Town of Nantucket. Land use classifications are based on assessors’ records provided by the town. 29

Figure IV-2. Distribution of land-uses by area within the watershed to Sesachacha Pond. 30

Figure IV-3. Parcels, Parcelized Watersheds, and Developable Parcels in the Sesachacha Pond watershed..... 35

Figure IV-4. Land use-specific unattenuated nitrogen load (by percent) to the Sesachacha Pond System watershed. “Overall Load” is the total nitrogen input within the watershed, while the “Local Control Load” represents only those nitrogen sources that could potentially be under local regulatory control..... 37

Figure IV-5. Sesachacha Pond embayment system sediment sampling sites (red symbols) for determination of nitrogen regeneration rates. Numbers are for reference to Table IV-3..... 41

Figure IV-6. Conceptual diagram showing the seasonal variation in sediment N flux, with maximum positive flux (sediment output) occurring in the summer months, and maximum negative flux (sediment up-take) during the winter months..... 43

Figure IV-7. Time course of average total nitrogen concentrations in Sesachacha Pond during non-open periods in summers of 2004 (top) and 2005 (bottom). The linear increase in total nitrogen is directly proportional to duration of pond closure..... 46

Figure V-1. Topographic map detail of Sesachacha Pond, Nantucket Island, Massachusetts. 48

Figure V-2. Salinity of Sesachacha Pond between 1967 and 1988 (from Kelly, 1988)..... 49

Figure V-3. Record of pond openings between 1997 and 2004 indicating the relative success of the opening (in days), as well average annual salinity levels (Curley, 2004)..... 50

Figure V-4. Historical shoreline change rates (1955-2003) in the area of Sesachacha Pond. 52

Figure V-5.	Bathymetry survey lines (yellow) followed by the boat in Sesachacha Pond. The final RMA2 grid used for hydrodynamic and water quality modeling is also shown as the white mesh.	54
Figure V-6.	Nantucket Harbor tides used for the water level outside Sesachacha Pond for the hydrodynamic model. Elevations are referenced to MLLW.	55
Figure V-7.	Area map detail of Edgartown Great Pond, Martha’s Vineyard, Massachusetts.	56
Figure V-8.	Water elevations during the breach event in Edgartown Great Pond.....	57
Figure V-9.	A comparison of the broad-crested weir model results with the recorded pond elevations during the breach event at Edgartown Great Pond.	58
Figure V-10.	Weir model results for a breach event at Sesachacha Pond. The blue line represents the predicted water elevation in the pond. These values were used as the boundary condition for the RMA2 hydrodynamic model of the pond.	60
Figure V-11.	Interpolated bathymetric contours of the final RMA2 computational mesh of Sesachacha Pond. Depth contours are relative to the MLLW.....	61
Figure VI-1.	2005 aerial photo showing monitoring station location in Sesachacha Pond that was used in the water quality analysis.....	65
Figure VI-2.	RMA-4 salinity dispersion model output for simulation of the spring 2004 opening of Sesachacha Pond. For this opening event, the inlet allowed tidal exchange with the Atlantic Ocean for 25 days before it closed again.....	68
Figure VI-3.	Comparison of measured (black circles) and modeled (red triangles) salinities through the summer of 2004, beginning with the spring breaching of an inlet to the Atlantic Ocean. The first two data points bracket the period of time that the inlet was open, and the Pond was tidally flushed. This breach period was simulated using the RMA-4 model of the Pond. Between May and November, the breach was closed, which prevented any tidal exchange. This period through the summer was simulated using the mass balance model. Results of the sensitivity analysis are also presented, showing model output using recharge rate determined by the Cape Cod Commission (CCC) and zero recharge.	69
Figure VI-4.	Model salinity target values are plotted against measured concentrations, together with the unity line, for the simulation period from May through November 2004. RMS error for this model verification run is 0.89 ppt and the R ² correlation coefficient is 0.75.	69
Figure VI-5.	RMA-4 total nitrogen dispersion model output for simulation of the spring 2004 opening of Sesachacha Pond. For this opening event, the inlet allowed tidal exchange with the Atlantic Ocean for 25 days before it closed again.	70
Figure VI-6.	Comparison of measured (black circles) and modeled (red triangles) total nitrogen concentrations through the summer of 2004, beginning with the spring breaching of an inlet to the Atlantic Ocean. The first two data points bracket the period of time that the inlet was open, and the Pond was tidally flushed. Between May and November, the breach was closed, which prevented any tidal exchange. Results of the sensitivity analysis are also presented, showing model output using recharge rate determined by the Cape Cod Commission (CCC) and zero recharge.	71
Figure VI-7.	Model total nitrogen calibration target values are plotted against measured concentrations, together with the unity line, for the simulation period from May through November 2004.. Computed correlation (R ²) and error (rms) for the model are also presented.....	71

Figure VII-1. Average watercolumn respiration rates (micro-Molar/day) from water collected throughout the Popponeset Bay System (Schlezinger and Howes, unpublished data). Rates vary ~7 fold from winter to summer as a result of variations in temperature and organic matter availability..... 77

Figure VII-2. Aerial Photograph of the Sesachacha Pond system in Falmouth showing locations of Dissolved Oxygen mooring deployments conducted in the summer of 2002. 77

Figure VII-3. Bottom water record of dissolved oxygen at the Sesachacha Pond station, summer 2002. Calibration samples represented as red dots. 79

Figure VII-4. Bottom water record of chlorophyll-a at the Sesachacha Pond station, summer 2002. Calibration samples represented as red dots. 79

Figure VII-5. Aerial photograph of the Sesachacha Pond system showing location of benthic infaunal sampling stations (red symbol). Station 1 in each of the transects is at the southern end of the pond (bottom). 82

Figure VIII-1. Comparison of measured (black circles) and modeled (red triangles) salinities through the summer of 2003 ($R^2=0.74$, RMS error=1.31 ppt). Present conditions with pond openings in Spring and Fall. 87

Figure VIII-2. Comparison of measured (black circles) and modeled (red triangles) TN concentrations through the summer of 2003 ($R^2=0.83$, RMS error=0.13 mg/L). Present conditions with pond openings in Spring and Fall..... 88

Figure VIII-3. Comparison of modeled 2003 salinities for case where the pond is breached only in the spring (thick black dot-dashed line) and also when it is breached an additional time mid-summer. Model results for the following 2004 spring- to-fall season (thin red dash dot line) show how salinities change if the mid-summer breach is performed again. 89

Figure VIII-4. Comparison of modeled 2003 TN for case where the pond is breached only in the spring (thick black line) and also when it is breached an additional time mid-summer (dot-dashed line). Model results for the following 2004 spring- to-fall season (thin red dash dot line) show how TN concentrations change if the mid-summer breach is performed again..... 89

LIST OF TABLES

Table IV-1. Primary Nitrogen Loading Factors used in the Sesachacha Pond MEP analyses. General factors are from MEP modeling evaluation (Howes & Ramsey 2001). Site-specific factors are derived from Barnstable data. *Data from MEP lawn study in Falmouth, Mashpee & Barnstable 2001.34

Table IV-2. Sesachacha Pond Nitrogen Loads. All values are kg N yr⁻¹.....37

Table IV-3. Rates of net nitrogen return from sediments to the overlying waters of Sesachacha Pond. These values are combined with the basin areas to determine total nitrogen mass in the water quality model (see Chapter VI). Measurements represent July -August rates. N = number of sites44

Table V-1. Tide datums reported by NOAA for Nantucket Harbor. Datum elevations are given relative to MLLW.....55

Table VI-1. Measured nitrogen concentrations and salinities for the Sesachacha Pond estuarine. “Data mean” values are calculated as the average of the separate yearly means. Data represented in this table were collected in 1992 through 2005 in Sesachacha Pond and the summer of 2005 in the Atlantic Ocean (offshore Pleasant Bay Inlet).....64

Table VI-2. Sub-embayment and surface water loads used for total nitrogen modeling of Sesachacha Pond, with total watershed N loads, atmospheric N loads, and benthic flux. These loads represent **present loading conditions** for the listed sub-embayments.....67

Table VI-3. Model TN concentrations and salinities verses inlet days open. For modeled Spring though Fall 2004 conditions.72

Table VI-4. Comparison of sub-embayment watershed loads used for modeling of present, build-out (scenarios “A” and “B”), and no-anthropogenic (“no-load”) loading scenarios of Sesachacha Pond. These loads do not include direct atmospheric deposition (onto the sub-embayment surface) or benthic flux loading terms.72

Table VI-5. **Build-out scenario** sub-embayment and surface water loads used for total nitrogen modeling of the Sesachacha Pond system, with total watershed N loads, atmospheric N loads, and benthic flux.....73

Table VI-6. **“No anthropogenic loading”** (“no load”) sub-embayment and surface water loads used for total nitrogen modeling of the Sesachacha Pond system, with total watershed N loads, atmospheric N loads, and benthic flux.....73

Table VII-1. Percent of time during deployment of in situ sensors that bottom water oxygen levels were below various benchmark oxygen levels.80

Table VII-2. Duration (% of deployment time) that chlorophyll a levels exceed various benchmark levels within the embayment system. “Mean” represents the average duration of each event over the benchmark level and “S.D.” its standard deviation. Data collected by the Coastal Systems Program, SMAST.....80

Table VII-3. Benthic infaunal community data for the Sesachacha Pond embayment system. Estimates of the number of species adjusted to the number of individuals and diversity (H') and Evenness (E) of the community allow comparison between locations. Samples represent surface area of 0.018 m², N/A indicates that numbers of individuals prevent calculation of species numbers @ 75 individuals.....83

Table VIII-1. Summary of Nutrient Related Habitat Health within the Sesachacha Pond Estuary on the eastern coast of Nantucket Island within the Town of Nantucket, MA, based upon assessment data presented in Chapter VII. The system is presently structured as a great salt pond consisting of a single basin formed from seawater entry to a coastal kettle pond.....85